



**NOTES:**

1. FILTER FABRIC SHALL HAVE AN AOS OF 40-85.
2. WOODEN FRAME SHALL BE CONSTRUCTED OF 2" X 4" CONSTRUCTION GRADE LUMBER.
3. WIRE MESH ACROSS THROAT SHALL BE A CONTINUOUS PIECE 30 INCH MINIMUM WIDTH WITH A LENGTH 4 FEET LONGER THAN THE THROAT. IT SHALL BE SHAPED AND SECURELY NAILED TO A 2" X 4" WEIR.
4. THE WEIR SHALL BE SECURELY NAILED TO 2" X 4" SPACERS 9 INCHES LONG SPACED NO MORE THAN 6 FEET APART.
5. THE ASSEMBLY SHALL BE PLACED AGAINST THE INLET AND SECURED BY 2" X 4" ANCHORS 2' LONG EXTENDING ACROSS THE TOP OF THE INLET AND HELD IN PLACE BY SANDBAGS OR ALTERNATE WIEGHTS.

MAXIMUM DRAINAGE AREA 1 ACRE

VILLAGE OF MAMARONECK  
STANDARD CONSTRUCTION DETAILS

PREPARED IN THE  
OFFICE OF THE  
VILLAGE ENGINEER

**CURB INLET PROTECTION**

DESIGNED BY: ARC, PE      CHECKED BY: ARC, PE  
DRAWN BY: ARC, PE      VOM Curb Inlet Protection.dwg



**VILLAGE OF MAMARONECK**  
VILLAGE MUNICIPAL BUILDING  
169 MT. PLEASANT AVENUE (3RD FLOOR)  
VILLAGE OF MAMARONECK, NY 10543  
PHONE: (914) 777-7731  
FAX: (914) 777-7792

PROJECT: DETAILS  
SCALE: NOT TO SCALE  
DATE: 03/13/2014

**SD-1D**